

Serial No. 10/629,703

Docket No. 200206985-3 US (1509-429)

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (*Previously presented*) An underfloor cable junction unit for installation beneath a raised floor, the space beneath the raised floor being arranged as a cooling air supply duct for devices adapted to be arranged on the raised floor, the raised floor having floor panels with cooling air outlets, the junction unit having (a) a top side, wherein the top side or at least a major part of it is open to enable passage of cooling air through the top side toward a floor panel of the raised floor, the panel including cooling air outlets, (b) connectors for connecting data cables for the devices to each other, (c) a structure for mounting the junction unit in the supply duct, and (d) lateral sides, the lateral sides or at least a major part of them being open for enabling cooling air to flow through the lateral sides and thereby form part of the cooling air supply duct while the cable junction unit is installed in the duct.

2. (*Previously presented*) The underfloor cable junction unit of claim 1, wherein the mounting structure is arranged to be mounted on a base floor on which the raised floor is posted.

3. (*Cancelled*)

Serial No. 10/629,703

Docket No. 200206985-3 US (1509-429)

4. (*Currently amended*) The underfloor cable junction unit of claim 1, having opposite faces and comprising rows of connectors for data cables, the rows being arranged on at least two levels, one above the other, ~~at at least one of the faces,~~ at least one of the faces of the junction unit having open slits between the rows of connectors to facilitate the passage of cooling air through the junction unit from face to face.

5. (*Cancelled*)

6. (*Currently amended*) An underfloor cable junction unit for installation in a raised-floor system used as cooling air supply duct, the junction unit having opposite faces and comprising rows of connectors arranged on at least two levels, one above the other, ~~at at least one of the faces,~~ at least one of the faces including open slits between the rows of connectors to facilitate passage of cooling air through the junction unit from face to face, the open slits thereby forming part of the cooling air supply duct while the cable junction unit is installed in the duct.

7. (*Previously presented*) The underfloor cable junction unit of claim 6, the junction unit having a top side, wherein the top side or at least a major part of it is open to enable the passage of cooling air through the top side and thereby form part of the cooling air supply duct while the cable junction unit is installed in the duct.

8. (*Previously presented*) The underfloor cable junction unit of claim 6, the junction unit having lateral sides, wherein the lateral sides or at least a major part of them are open and

Serial No. 10/629,703**Docket No. 200206985-3 US (1509-429)**

thereby form part of the cooling air supply duct while the cable junction unit is installed in the duct.

9. (*Currently amended*) An underfloor cable junction unit with structure and dimensions for enabling it to be installed below a raised floor of for installation in a raised-floor system, the junction unit having opposite faces and comprising slide-in data connector units able to be slid from outside into the junction unit at at least one of its faces, the slide-in connector units being arranged on at least two levels in the junction unit, one above the other.

10. (*Original*) The underfloor cable junction unit of claim 9, wherein the slide-in connector units are fixed to the junction unit in a dismountable manner to enable them to be removed, replaced or changed in their position or enable further slide-in units to be mounted, without dismounting the junction unit.

11. (*Currently amended*) The underfloor cable junction unit of claim 9, wherein the slide-in connector units have data connector rows, at least some of the connector rows, being including at least one of copper data cable connector rows [[or]] and optical fiber connector rows.

12. (*Currently amended*) The underfloor cable junction unit of claim 11, having optical fiber connector rows with ~~a connector type which enables~~ connectors for enabling pre- fabricated optical break-out cables with pre-installed cable connectors to be plugged-in at the permanent-cable connection side of the junction unit connectors, without using a splice box.

Serial No. 10/629,703

Docket No. 200206985-3 US (1509-429)

13. (*Original*) The underfloor cable junction unit of claim 9, arranged to accommodate slide-in connector units at two opposing faces of the junction unit.

14. (*Currently amended*) ~~The underfloor cable junction unit of claim 9, wherein~~
An underfloor cable junction unit for installation in a raised-floor system, the junction unit having opposite faces and comprising slide-in data connector units able to be slid from outside into the junction unit at at least one of its faces, the slide-in connector units being arranged on at least two levels in the junction unit, one above the other, the junction unit has having an inside, and wherein connectors of the slide-in connector units are arranged such that permanent cable connections are at an inner side of the connectors facing the inside of the junction unit and plug-in patch cable connections are at an outward-facing side of the connectors.

15. (*Currently amended*) ~~The underfloor cable junction unit of claim 9, wherein~~
An underfloor cable junction unit for installation in a raised-floor system, the junction unit having opposite faces and comprising slide-in data connector units able to be slid from outside into the junction unit at at least one of its faces, the slide-in connector units being arranged on at least two levels in the junction unit, one above the other, the slide-in connector units have- having rows of connectors, the connectors including enclosures.

16. (*Currently amended*) An underfloor cable junction unit with structure and dimensions for enabling it to be installed below a raised floor of a raised-floor system unit

Serial No. 10/629,703**Docket No. 200206985-3 US (1509-429)**

including rows of data connectors for installation in a raised floor system, the junction unit having a frame structure with a frame, the frame comprising portal front parts and sidebars connecting the front parts, such that the portal front parts are opposite each other.

17. *(Previously presented)* The underfloor cable junction unit of claim 16, wherein both front parts are open at least at their lower parts to enable bunches of permanent data cables to pass through the junction unit, whereby the permanent cable bunches are encompassed and thereby guided.

18. *(Original)* The underfloor cable junction unit of claim 16, wherein several mounting positions are provided for the sidebars to enable them to be mounted at different heights.

19. *(Original)* The underfloor cable junction unit of claim 16, wherein the sidebars are mounted to the front parts in a dismountable manner to enable them to be replaced or their mounting height to be changed.

20. *(Currently amended)* ~~The underfloor cable junction unit of claim 16, which is~~
An underfloor cable junction unit with rows of data connectors for installation in a raised-floor system, the junction unit having a frame structure with a frame, the frame comprising portal front parts and sidebars connecting the front parts, such that the portal front parts are opposite each other, the underfloor cable junction unit being arranged to be height adjustable.

Serial No. 10/629,703

Docket No. 200206985-3 US (1509-429)

21. *(Currently amended)* ~~The underfloor cable junction unit of claim 16, which is~~
An underfloor cable junction unit with rows of data connectors for installation in a
raised-floor system, the junction unit having a frame structure with a frame, the frame
comprising portal front parts and sidebars connecting the front parts, such that the portal front
parts are opposite each other, the underfloor cable junction unit being arranged to be width
adjustable.

22. *(Previously presented)* An underfloor cable junction unit for installation in a raised-floor system, the junction unit having faces and lateral sides, wherein at least one of the faces is equipped with rows of data connectors, and at least one horizontal sidebar is arranged at each of the lateral sides, the at least one horizontal sidebar being arranged to enable permanent cables coming from the inner side of said connector rows to pass above and outwardly of the sidebar downwardly to a base floor and to be fixed to the sidebar.

23. *(Previously presented)* The underfloor cable junction unit of claim 22, further comprising patch cable guiding elements arranged laterally at at least one of the faces of the junction unit, said guiding elements enabling patch data cables plugged into data connectors of the connector rows to be guided laterally on the face of the junction unit downwardly to a base floor.

24. *(Previously presented)* The underfloor cable junction unit of claim 22, wherein both faces are open at least at their lower parts to enable bunches of permanent data cables

Serial No. 10/629,703

Docket No. 200206985-3 US (1509-429)

to pass through the junction unit, whereby the permanent cable bunches are encompassed and thereby guided.

25. *(Previously presented)* A computer center having a raised floor on which computers are arranged, said raised floor being arranged as cooling air supply duct for the computers and having floor panels with cooling air outlets, said raised floor being equipped with underfloor data cable junction units by which the computers are connected to permanent data cables running under the raised floor, each junction unit having a top side, wherein the top side or at least a major part of it is open to enable passage of cooling air through the top side toward a floor panel with cooling air outlets.

26. *(Previously presented)* A computer center having a raised floor on which computers are arranged, said raised floor including air outlets for supplying cooling air to the computers, space beneath the raised floor being arranged as cooling air supply duct for the computers, said raised floor being equipped with underfloor cable junction units by which the computers are connected to permanent data cables running under the raised floor, each junction unit having opposite faces and comprising rows of connectors arranged on at least two levels, one above the other, at at least one of the faces, wherein open slits are in at least one of the faces between the rows of connectors to facilitate passage of cooling air through the junction unit from face to face.

27. *(Previously presented)* A computer center having a raised floor on which computers are arranged, said raised floor being equipped with underfloor cable junction units

Serial No. 10/629,703**Docket No. 200206985-3 US (1509-429)**

by which the computers are connected to permanent data cables running under the raised floor, each junction unit having opposite faces and comprising slide-in connector units able to be slid from outside into the junction unit at at least one of its faces, the slide-in connector units being arranged on at least two levels in the junction unit, one above the other.

28. (*Currently amended*) [[A]] The computer center of claim 27, wherein having a raised floor on which computers are arranged, said raised floor being equipped with underfloor cable junction units by which the computers are connected to permanent data cables running under the raised floor, each junction unit having has a frame structure with a frame, the frame comprising portal front parts and sidebars connecting the front parts, such that the portal front parts are arranged opposite each other, the side bars carrying the slide-in connector units.

29. (*Previously presented*) A computer center having a raised floor on which computers are arranged, said raised floor being equipped with underfloor cable junction units by which the computers are connected to permanent data cables running under the raised floor, each junction unit having faces and lateral sides, wherein at least one of the faces is equipped with rows of connectors, and at least one horizontal sidebar is arranged at each of the lateral sides, the at least one horizontal sidebar being arranged to enable permanent cables coming from the inner side of connector rows to pass above and outwardly of the sidebar downwardly to a base floor and to be fixed to the sidebar.

30. (*Previously presented*) The computer center of claim 29, further comprising:

Serial No. 10/629,703**Docket No. 200206985-3 US (1509-429)**

active network elements and network element junction units, wherein the permanent data cables permanently connect the underfloor cable junction units and the network element junction units,

first patch cables for the connection of the computers with the underfloor cable junction units, and

second patch cables for the connection of the active network elements with the network element junction units.

31. *(Previously presented)* A computer center having a raised floor on which computers are arranged, said raised floor including air outlets for supplying cooling air to the computers, space beneath the raised floor being arranged as cooling air supply duct for the computers, said raised floor being equipped with underfloor cable junction units by which the computers are connected to permanent data cables running under the raised floor, each junction unit having first, second, third, and fourth legs on a subfloor beneath the raised floor, the first and second legs being in a first plane, the third and fourth legs being in a second plane parallel to the first plane, the first and third legs being in a third plane at right angles to the first and second planes, and the second and fourth legs being in a fourth plane parallel to the third plane; a first sidebar connected between the first and second legs; a second sidebar connected between the third and fourth legs; the permanent data cables extending longitudinally in the direction of the first and second sidebars and between the legs; a first face part extending between the first and third legs; a second face part extending between the second and fourth legs; slide-in units on one of the face parts, the slide-in units including first data connectors having longitudinal axes extending parallel to the sidebars for connection to

Serial No. 10/629,703**Docket No. 200206985-3 US (1509-429)**

data cables having ends positioned at opposite sides of the first data connectors along the longitudinal axes, the junction unit being arranged so cooling air in the supply duct can flow under and over each of the sidebars and face parts, and an opening for flow of cooling air extending from just above the subfloor to an air outlet between the sidebars and face parts.

32. (*Previously presented*) The computer center of claim 31, wherein each of the face parts includes a row of second data connectors, the second data connectors having longitudinal axes extending parallel to the sidebars for connection to data cables having ends positioned at opposite sides of the second data connectors along the longitudinal axes.

33. (New) The underfloor cable junction unit of claim 1, which is arranged to be adjustable in width and height to enable lowering of the unit through any standard sized module opening which is present when a module panel of a discrete modular raised floor system is removed.

34. (New) The unit of claim 9, in combination with the raised-floor system, wherein the unit is below the raised floor of the raised-floor system, and is on a structure on a base floor beneath the raised floor.

35. (New) The unit of claim 16, in combination with the raised-floor system, wherein the unit is below the raised floor of the raised-floor system, and is on a structure on a base floor beneath the raised floor.